

| WIRING KEY | | | |
|------------|----------------|-------------------------|--|
| COLOR | COMPONENT | TYP. MAX CURRENT (A) | |
| RED | MAIN POWER | 11.6 | |
| BLK | GROUND | 20A Limit | |
| | | | |
| BRN | PATTERN 1 | .002 | |
| ORG | PATTERN 2 | .002 | |
| YEL | ALLEY LEFT | .002 | |
| GRN | ALLEY RIGHT | .002 | |
| BLU | WORKLIGHT | .002 | |
| VIO | PATTERN SELECT | .002 | |

REAR OF VEHICLE

| | WIRING KEY | |
|-------|-----------------|-------------------------|
| COLOR | COMPONENT | TYP. MAX CURRENT (A) |
| WHT | GROUND | 1.0 ` ´ |
| BRN | RUNNING LIGHTS | 0.1 |
| YEL | STOP/TURN LEFT | 0.5 |
| GRN | STOP/TURN RIGHT | 0.5 |
| RED | N/A | N/A |
| | | |

SPECIFICATIONS

- 1. FLASH MODE: MAXIMUM 150 FPM
- 2. VOLTAGE (NOMINAL): 12-24 VDC
- 3. CURRENT (NOMINAL): 12.6 A @ 12 VDC
- 4. CONNECTION: 14, 18 AND 24 AWG WIRES
- 5. MOUNTING: 4-BOLT THROUGH MOUNTING KIT
- 6. BASE MATERIAL: ALUMINUM/POLYCARBONATE
- 7. LENS MATERIAL: POLYCARBONATE
- 8. WITH HANDHELD CONTROLLER: NO

