



REVISION HISTORY		
REV.	DESCRIPTION	DATE
01	PRELIMINARY RELEASE PER LM14214	2014-05-22
02	REVISED PER LM14214	2014-06-02
A	INITIAL RELEASE PER LM14214	2014-06-26

15' [4572] CORD W/DUAL SWITCH LIGHTER ADAPTER

SPECIFICATIONS

- CERTIFICATIONS: **CE**; ECE R10; SAE J845 (DEC 2007) CLASS 1 YELLOW (AMBER); CA Title 13 Class B; IP-35C For a Category 2 Enclosure
 Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.
- FLASH MODE: DOUBLE : 75 ± 5 FLASHES PER MINUTE
 QUAD : 75 ± 5 FLASHES PER MINUTE
 QUINT : 75 ± 5 FLASHES PER MINUTE
- VOLTAGE (NOMINAL): 12 to 24 VDC
- VOLTAGE (EXTREME): 9.0 to 32.0 VDC
- CURRENT (PEAK): 6A (@ 12 VDC NOMINAL)
- POWER (MAXIMUM): 76.8W (@ 12 VDC NOMINAL)
- TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)
- CONNECTION: 15' CORD W/DUAL SWITCH LIGHTER ADAPTER
- MOUNTING: MAGNET
- BASE MATERIAL: POLYCARBONATE
- LENS MATERIAL: POLYCARBONATE
- PRODUCT WEIGHT: 4.5 LBS (2.03 Kg)

NOTES:
 1. DIMENSIONS IN INCHES [MILLIMETERS (FOR REFERENCE)]

SCALE 1:4.5		APPROVALS	DATE
CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED:03		DRAWN BY SNS	2014-06-02
		CHECKED	2014-06-03
TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES ARE:		MECH. ENG. NMT	2014-06-02
		ELEC. ENG. TJT	2014-06-02
MILLIMETERS DECIMALS XX. ± 1.0mm XX.X ± 0.5mm		INCHES DECIMALS X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	ANGLES ± 0.5°
			FRACTIONS ± 1/64
THIRD ANGLE PROJECTION		TEST ENG. JRT	2014-06-16
		SALES. LAT	2014-06-03

ECCO® Electronic Controls Co.
 833 West Diamond Street, Boise, ID 83705
 800-635-5900
 www.eccolink.com

LED MINIBAR, 8 HEAD, 12-24VDC, CAC, C1, MG

CUSTOMER PART NO. 5590CAC-MG		PRODUCT SERIES: 5500	
SIZE: A	DWG. NO. 5590CAC-MG	REV. A	
Electronically Controlled Use Latest Copy		SHEET 1 OF 1	Project: LM14214 Date Created: 2014-05-13