

REVISION HISTORY							
REV.	DESCRIPTION	DATE					
Н	REVISE PER P08054	2011-09-23					
J	REVISE PER EC4447	2017-08-01					
K	REVISED PER EC7101	2024-02-06					

3-16 AWG WIRES RED - POSITIVE(+) BLACK - NEGATIVE(-) WHITE - DUAL/QUAD

FGS. PRODUCT CHART								
FGS. NO.	COLOR	J1318 (MAY 1998)						
6550A	AMBER	CLASS 2						
6550B	BLUE	CLASS 2						
6550C	WHITE	CLASS 2						
6550G	GREEN	-						

SPECIFICATIONS

1. CERTIFICATIONS: SAE (SEE CHART)

Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols.

Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.

FLASH MODE: DOUBLE: 80 ± 5 FLASHES PER MINUTE
 QUAD: 65 ± 5 FLASHES PER MINUTE

3. VOLTAGE (NOMINAL): 12 to 48 VDC4. VOLTAGE (EXTREME): 9.0 to 56.0 VDC

5. CURRENT (PEAK): 2.4A (@ 12 VDC NOMINAL)

6. POWER (MAXIMUM): 30W (@ 12 VDC NOMINAL)

7. TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)

8. CONNECTION: 3-16 AWG WIRES

9. MOUNTING: FLANGE MOUNT, PIPE MOUNT

10. BASE MATERIAL: GLASS FILLED NYLON

11. LENS MATERIAL: POLYCARBONATE

12. PRODUCT WEIGHT: 1.2 LBS (0.54 Kg)

NOTES:

4.9 [124]

PROPRIETARY AND CONFIDENTIAL INFORMATION

THIS DRAWNIC AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN ARE THE PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS ECCO SAFTY GROUP AFFILIATES ("ECCO") AND IS SUSED IN CONFIDENCE TO RECIPIENT FOR ENGINEERING INFORMATION PURPOSO ONLY. THIS DRAWNIC AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN MAY NOT BE USED. COPIED, REPRODUCED OR OTHER WISE DISCLOSED IN PART OR IN WHOLE TO THEN DEATHER OF USED FOR ANY OTHER PURPOSE WINDOWN FOR ECCO WRITER CONSETT. ECCO PRESENTS ALL PRICE COPIED, RECORD TO THE PROPERTY OF THE PURPOSE WINDOWN FOR EXAMPLE OF THE PURPOSE OF THE PURPO

1. DIMENSIONS IN INCHES[MILLIMETERS (FOR REFERENCE)]

SCALE 1:2.5			APP	ROVALS	DATE				
CAD GENERATED DRAWING DO NOT MANUALLY UPDATE.			DRAWN BY A	ABD	2024-02-02		ECC	www.eccolin	k.com
			CHECKED	BTK	2024-02-05	₹			
TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:		MECH. ENG.	PH	2024-02-05	Americas (800) 635-5900 Europe +44 (0)113 237 5340 Asia Pacific +61 (0)3 63322444				
	CHES DECIMALS	ANGLES ± 0.5°	ELEC. ENG.	SPO	2024-02-02	STROBE,360*,12-48 VDC,7/10JOULES			
XX.X ± 0.5mm X.)	X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	FRACTIONS	TEST ENG.	JRT	2024-02-05	CUSTOMER PAR			
	X.XXX ± 0.02 ± 1/64 IIRD ANGLE PROJECTION		SALES.			SEE CH	1AKI		
IFIRD ANGLE PROJECTION					SIZE: A	DWG. NO.	6550X	REV.	
			Electronically Controlled Use Latest Copy			SHEET 1 OF 1	Project: 98003	Date Created: 1998-07-20] K