



REVISION HISTORY		
REV.	DESCRIPTION	DATE
01	REVISED PER P11045	2011-06-02
A	INITIAL RELEASE PER P11045	2011-06-16

## SPECIFICATIONS

- CERTIFICATIONS: **CE**; e; AMECA/SAE J1318 (MAY 1998), CLASS 2, YELLOW (AMBER) COLOR;  
 Note: Unique components, accessories, and hardware kits are not typically included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.
- FLASH MODE: QUAD : 65 ± 5 FLASHES PER MINUTE  
 DOUBLE : 65 ± 5 FLASHES PER MINUTE
- VOLTAGE (NOMINAL): 12 to 24 VDC
- VOLTAGE (EXTREME): 12.0 to 32.0 VDC
- CURRENT (PEAK): 4.24A (@ 12 VDC NOMINAL)
- POWER (MAXIMUM): 54.272W (@ 12 VDC NOMINAL)
- TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)
- CONNECTION: ZIP CORD W/LIGHTER ADAPTER
- MOUNTING: VACUUM/MAGNET MOUNT
- BASE MATERIAL: ALUMINUM
- LENS MATERIAL: POLYCARBONATE
- PRODUCT WEIGHT: 2.2 LBS (0.99 Kg)

NOTES:  
 1. DIMENSIONS IN INCHES[MILLIMETERS (FOR REFERENCE)]

SCALE 1:3.25		APPROVALS	DATE
CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED:A+		DRAWN BY BND	2011-06-02
		CHECKED MDH	2011-06-03
TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES ARE:		MECH. ENG. JLA	2011-06-02
MILLIMETERS DECIMALS XX. ± 1.0mm XX.X ± 0.5mm	INCHES DECIMALS X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	ANGLES ± 0.5° FRACTIONS ± 1/64	ELEC. ENG. TJT 2011-06-02
		TEST ENG. JRT	2011-06-13
		SALES. WNH	2011-06-07
THIRD ANGLE PROJECTION			

**ECCO**® Electronic Controls Co.  
 833 West Diamond Street, Boise, ID 83705  
 800-635-5900  
 www.eccolink.com

**STROBE, 360\*, 12-24VDC, 5-12JLS, S/D, VM**

CUSTOMER PART NO. <b>SEE CHART</b>		PRODUCT SERIES: <b>6600</b>
SIZE: A	DWG. NO. <b>6670X-VM</b>	REV. A
SHEET 1 OF 1	Project: P11045	Date Created: 2011-05-23