



 REVISION HISTORY

 REV.
 DESCRIPTION
 DATE

 A
 INITIAL RELEASE PER LM14240
 2016-03-07

 B
 REVISE PER LM14240
 2016-04-13

 C
 REVISED PER EC7112
 2025-06-19

## **SPECIFICATIONS**

CERTIFICATIONS: C€:

Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.

- 2. RAW LUMENS: 53 lumens
- 3. EFFECTIVE LUMENS: 53 lumens
- 4. ILLUMINANCE: lux
- 5. PEAK BEAM INTENSITY: Candela
- 6. EFFICACY: lm/W
- 7. CORRELATED COLOR TEMPERATURE: 4516K
- 8. VOLTAGE (NOMINAL): 12 VDC
- 9. VOLTAGE (EXTREME): 10 to 16 VDC
- 10. CURRENT (PEAK): 0.08A (@ 12 VDC NOMINAL)
- 11. POWER (MAXIMUM): 1.0W (@ 12 VDC NOMINAL)
- 12. TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)
- 13. CONNECTION: 2 20 AWG WIRES
- 14. MOUNTING: FLUSH
- 15. HOUSING MATERIAL: PENDING
- 16. LENS MATERIAL: PENDING
- 17. PRODUCT WEIGHT: 0.1 LBS (0.05 Kg)

DIMENSIONS, ILLUSTRATIONS, SPECIFICATIONS AND CERTIFICATIONS CONTAINED IN THIS DOCUMENT ARE TYPICAL OF THE ACTUAL PRODUCT AND ARE SUBJECT TO CHANGE. ECCO ENGINEERING DOES NOT MAINTAIN FORMAL DESIGN CONTROL OF THIS PRODUCT.

MOUNTING DISCLAIMER:

MOUNTING MEASUREMENT IS FOR REFERENCE ONLY. MEASURE BEFORE DRILLING.

## NOTES: 1. FOR INTERIOR USE ONLY 2. ROHS COMPLIANT

**BOTTOM VIEW** 

3. DIMENSIONS IN INCHES[MILLIMETERS (FOR REFERENCE)]

PROPRIETARY AND CONFIDENTIAL INFORMATION

THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HERBIN ARE THE PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS

ECCO SAFETY GROUP AFFLIATES (PECCO) AND IS SISUED IN CONFIDENCE TO RECIPIENT FOR ENGINEERING INFORMATION PURPOSES ONLY. THIS

DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HERBIN MAY NOT BE USED, COPED, REPRODUCED OR OTHERWISE DISCLOSED IN PART

TRADEMARK AND OTHER PROPERTIESEY RICHEST ON THE DESIGN MANUFACTURING, EXPOSITION TO THE DESIGN AND OTHER PROPEDIATED WISE AND SALES RIGHTS

THERETO, THIS DRAWING IS SUBJECT TO RECALL BY ECCO AT ANY TIME. AND YOUR POSSESSION AND/OR USE CONSTITUTES ACCEPTANCE OF THESE

TERMS. 2013 ELECTRONIC CONTROLS COMPANY.

	SCALE 1:2			APPROVALS DATE			123					
	CAD C	VING	DRAWN BY	ABD	2024-01-24	ECCO www.eccolink.com						
	DO NO	DATE.	CHECKED	BTK	2024-01-24							
	TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:			MECH. ENG.	JLA	2024-01-24	Americas (800) 635-5900   Europe +44 (0)113 237 5340   Asia Pacific +61 (0)3 6332244					3 63322444
	MILLIMETERS DECIMALS	METERS DECIMALS INCHES DECIMALS ± 0.5°		ELEC. ENG.	JES	2024-07-30	INTERIOR LIGHT, EW022X					
	XX. ± 1.0mm XX.X ± 0.5mm	X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	FRACTIONS	TEST ENG.	JRT	2024-05-29	CUSTOMER					
-		2.0		SALES.			SEE	$\neg$	IAKI			
T T,	THIRD ANGLE PROJECTION						SIZE: A	`	DWG. NO.	EW022X		REV.
S				Electronically Controlled Use Latest Copy			SHEET 1 C	OF 1	Project: LM14240	Date Created: 2	2015-11-11	C