



REVISION HISTORY		
REV.	DESCRIPTION	DATE
01	PRELIMINARY RELEASE PER LM13214	2013-10-28
Α	INITIAL RELEASE PER LM13214	2013-12-12

## **SPECIFICATIONS**

**CERTIFICATIONS:** 

Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.

- 2. LUMINOUS FLUX: 4500 lumens
- 3. ILLUMINANCE: lux
- 4. PEAK BEAM INTENSITY: Candela
- 5. EFFICACY: 67.9 lm/W
- 6. CORRELATED COLOR TEMPERATURE: K
- 7. VOLTAGE (NOMINAL): 12 to 24 VDC
- 8. VOLTAGE (EXTREME): 10 to 30 VDC
- 9. CURRENT (PEAK): 4.8A (@ 12 VDC NOMINAL)
- 10. POWER (MAXIMUM): 66.3W (@ 12 VDC NOMINAL)
- 11. TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)

REV.

- 12. CONNECTION: 2 CONDUCTOR CABLE
- 13. MOUNTING: BRACKET MOUNT
- 14. HOUSING MATERIAL: ALUMINUM
- 15. LENS MATERIAL: POLYCARBONATE
- 16. PRODUCT WEIGHT: 5.5 LBS (2.48 Kg)

## **NOTES:** 1. DIMENSIONS IN INCHES[MILLIMETERS (FOR REFERENCE)]

NON DISCLOSURE AGREEMENT

THIS DRAWING AND THE DESIGN IT DISCLOSES ARE THE PRIVATE PROPERTY OF ECCO. AND IS ISSUED IN CONDIDENCE FOR ENGINEERING INFORMATION. ONLY, THE DRAWING AND / OR DESIGN MAY NOT BE USED, COPPIED, REPRODUCED, OR O'NIERWISE DISCLOSED IN PART OR, AS A WHOLE TO OUTSIDERS COUSED FOR ANY OTHER PURPOSE WITHOUT THE PRIOR WRITTEN CONSENT OF ECCO. THE DRAWING IS SUBJECT TO RECALL AT ANY TIME, YOUR POSSESSION OF THIS DECIMENT ACCEPTANCE OF THESE TERMS, © 2013 ECCO.

