

Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.

2. FLASH MODE: FLASH: ± 5 FLASHES PER MINUTE

RIGHT SWEEP: ± 5 FLASHES PER MINUTE LEFT SWEEP: ± 5 FLASHES PER MINUTE

- 3. VOLTAGE (NOMINAL): 12 to 24 VDC
- 4. VOLTAGE (EXTREME): 11 to 30 VDC
- 5. CURRENT (PEAK): 4A (@ 12 VDC NOMINAL)
- 6. POWER (MAXIMUM): 24.W (@ 12 VDC NOMINAL)
- 7. TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)
- 8. CONNECTION: 2 18 AWG WIRES
- 9. MOUNTING: BRACKET MOUNT
- 10. BASE MATERIAL: ALUMINUM
- 11. LENS MATERIAL: POLYCARBONATE
- 12. PRODUCT WEIGHT: 4.3 LBS (1.94 Kg)

NOTES:

1. DIMENSIONS IN INCHES[MILLIMETERS (FOR REFERENCE)]

DISCLAIMER

DIMENSIONS, ILLUSTRATIONS, SPECIFICATIONS, AND CERTIFICATIONS CONTAINED IN THIS DOCUMENT ARE TYPICAL OF THE ACTUAL PRODUCT AND ARE SUBJECT TO CHANGE. ECCO ENGINEERING DOES NOT MAINTAIN FORMAL DESIGN CONTROL OF THIS PRODUCT.

MOUNTING DISCLAIMER

MOUNTING MEASUREMENT IS FOR REFERENCE ONLY. MEASURE BEFORE DRILLING.

	SCALE 1:6			APPROVALS		DATE	(de	COOP.			
			DRAWN BY ABD		2016-04-19	(3	www.eccolink.com			m	
	DO NOT MANUALLY UPDATE. MODEL REFERENCED:01 TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:			CHECKED	ABB	2016-04-20					
Ī				MECH. ENG.	JLA	2016-04-19	Americas (800) 635-5900 Europe +44 (0)113 237 5340 Asia Pacific +61 (0)3 63322444				
Ī	MILLIMETERS DECIMALS	± 0.5°		ELEC. ENG.	TJT	2016-04-25	XT3 SERIES ARROWSTIK KIT 30"				
	XX. ± 1.0mm XX.X ± 0.5mm	X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	FRACTIONS	TEST ENG.	JRT	2016-04-20	CUSTOMER PART NO.			PRODUCT SERIES:	
+	THIRD ANGLE PROJECTION		± 1/64	SALES.	GLB	2016-04-25	37038AS				
<u>(.</u>							SIZE: A	DWG. NO.	7038	BAS REV.	
5	7			Electronically Controlled Use Latest Copy			SHEET 1 OF 1	Project: LM14260	Date Cre	ated: 2015-12-10 B	